

**GMCH.EX3940  
Wet-chemical Residential Range-top Extinguisher Units**[Page Bottom](#)**Wet-chemical Residential Range-top Extinguisher Units**[See General Information for Wet-chemical Residential Range-top Extinguisher Units](#)**GUARDIAN SAFETY SOLUTIONS INTERNATIONAL INC**

EX3940

SUITE 230  
8701 CARPENTER FWY  
DALLAS, TX 75247 USA

Models 1384-A and 1384-ASH, 2-1/2 lb. capacity, stored pressure type, wet chemical automatic extinguisher units designed to discharge wet chemical solution from fixed nozzles for the extinguishment of fires occurring on conventional residential gas or electric range tops, not exceeding 36 in. width, which are ventilated by a under-the-cabinet exhaust hood. These units are intended for use in ambient temperatures between +32 F and +120 F.

The Model 1384-A and 1384-ASH extinguisher units have demonstrated the capability of operating automatically within 90 s after autoignition of a 10 in. diameter cooking vessel when installed in accordance with the manufacturer's installation manual.

A description of the Model 1384-A and 1384-ASH extinguisher units along with their design and installation limitations are contained in the installation manual (p/n 71758-S) dated September 1989 (revised August 2000), and addendum (p/n 71757-3) dated August 2000. A copy of these manuals are available from the Listee.

Models 1384-B, 4.9 lb. capacity, stored pressure type, wet chemical automatic extinguisher units designed to discharge wet chemical solution from fixed nozzles for the extinguishment of fires occurring on conventional residential gas or electric range tops, not exceeding 36 in. width, which are ventilated by a under-the-cabinet exhaust hood. These units are intended for use in ambient temperatures between +32 F and +120 F.

The Model 1384-B extinguisher units have demonstrated the capability of operating automatically within 90 s after autoignition of a 10 in. diameter cooking vessel when installed in accordance with the manufacturer's installation manual.

A description of the Model 1384-B extinguisher units along with their design and installation limitations are contained in the installation manual (p/n 71758-B) dated May 1, 2011 (revised September 2012). A copy of these manuals are available from the Listee.

Model G300-A, 5 lb. capacity, stored pressure type, wet chemical automatic extinguisher unit designed to discharge wet chemical solution from fixed nozzles for the extinguishment of fires occurring on conventional residential gas or electric range tops not exceeding 36 in. width (gas) or 42 in. width (electric), which are ventilated by a under-the-cabinet exhaust hood. These units are intended for use in ambient temperatures between +32 F to +120 F.

A description of the Model G300-A extinguisher unit along with its design and installation limitations is contained in the installation manual (p/n G310A-A) dated February 20, 2007. A copy of this manual is available from the Listee.

Model G300-B, 4.9 lb. capacity, stored pressure type, wet chemical automatic extinguisher unit designed to discharge wet chemical solution from fixed nozzles for the extinguishment of fires occurring on conventional residential gas or electric range tops not exceeding 36 in. width (gas) or 42 in. width (electric), which are ventilated by a under-the-cabinet exhaust hood. These units are intended for use in ambient temperatures between +32 F to +120 F.

A description of the Model G300-B extinguisher unit along with its design and installation limitations is contained in the installation manual (p/n G310A-B) dated May 1, 2011 (revised September 2012). A copy of this manual is available from the Listee.

Model G500-B, 4.9 lb. capacity, stored pressure type, wet chemical automatic extinguisher unit designed to discharge wet chemical solution from fixed nozzles for the extinguishment of fires occurring on conventional residential gas or electric range tops not exceeding 36 in. width (gas) or 42 in. width (electric), which are ventilated by a under-the-cabinet exhaust hood. These units are intended for use in ambient temperatures between +32 F to +120 F.

A description of the Model G500-B extinguisher unit along with its design and installation limitations is contained in the installation manual (P/N G310A-B) dated May 1, 2011 (revised September 2012), and addendum (p/n G310A-B-G500) dated March 1, 2013.

Models G600-B and G600B-C, 4.9 lb. capacity, stored-pressure type, wet chemical automatic extinguisher unit designed to discharge wet chemical solution from fixed nozzles for the extinguishment of fires occurring on conventional residential gas or electric range tops not exceeding 30 in. width, which are ventilated by a either an under-the-cabinet microwave/exhaust hood combination or a

flat-faced (underside) exhaust hood. These units are intended for use in ambient temperatures between +32 F to +120 F.

A description of the Models G600-B and G600B-C extinguisher units along with its design and installation limitations is contained in the installation manual (P/N G610B) dated April, 2016 (rev. 0).

[Last Updated](#) on 2016-04-25

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".