

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-2155107-0
Report Reference EX3940-20160425
Date 31-Jan-2022

Issued to: GUARDIAN SAFETY SOLUTIONS INTERNATIONAL INC
SUITE 230
8701 CARPENTER FWY DALLAS, TX 75247
United States

This is to certify that
representative samples of GMCH - Wet-chemical Residential Range-top Extinguisher
Units
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-2155107-0
Report Reference EX3940-20160425
Date 31-Jan-2022

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
G600-B, 4.9 lb. (2222 g) capacity, designed to discharge wet chemical solution from fixed nozzles for the extinguishment of fires occurring on conventional residential gas or electric range tops not exceeding 30 in. width, which are ventilated by either an under-the-cabinet microwave/exhaust hood combination or a flat-faced (underside) exhaust hood. These units are intended for use in ambient temperatures between +32 F to +120 F (0 C to + 49 C). A description of the extinguisher units along with its design and installation limitations is contained in the installation manual (P/N G610B) dated April, 2016 (rev. 0). A copy of these manuals are available from the Listee.	Stored pressure type
G600B-C, 4.9 lb. (2222 g) capacity, designed to discharge wet chemical solution from fixed nozzles for the extinguishment of fires occurring on conventional residential gas or electric range tops not exceeding 30 in. width, which are ventilated by either an under-the-cabinet microwave/exhaust hood combination or a flat-faced (underside) exhaust hood. These units are intended for use in ambient temperatures between +32 F to +120 F (0 C to + 49 C). A description of the extinguisher units along with its design and installation limitations is contained in the installation manual (P/N G610B) dated April, 2016 (rev. 0). A copy of these manuals are available from the Listee.	Stored pressure type



Bruce Mahrenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>